

> Tabella selezione nastro

colore										
NERO  BK	BLU  BE	GRIGIO  GR	ROSSO  RD	BIANCO  WH	MARRONE  BW	VERDE  VE	GIALLO  YE	GIALLO/ VERDE  YG	min./ mult. ord. (pz)	
15 × 10		(15 mm × 10 m × 0,15 mm)								
NA4015	NA4115	NA4215	NA4315	NA4415	NA4515	NA4715	NA4815	NA4615	100	
19 × 25		(19 mm × 25 m × 0,15 mm)								
NA4019	NA4119	NA4219	NA4319	NA4419	NA4519	NA4719	NA4819	NA4619	120	
25 × 25		(25 mm × 25 m × 0,15 mm)								
NA4025	NA4125	NA4225	NA4325	NA4425	NA4525	NA4725	NA4825	NA4625	96	



Conformità
EN 60454-3-1

Autoestinguente (EN 60454)

Temperatura di esercizio
0 °C / +105 °C

Rigidità dielettrica (EN 60454)
40 kV/mm

Resistenza a trazione (EN 60454)
30 N/10 mm

Allungamento ultimo (EN 60454)
180% - 170 %

Adesività (EN 60454)
1,8 N/10 mm



Certificato
IMQ