



590.YM67B6

COMANDO FRONTALE LUCCHETTABILE

IP65 standard 67x67mm Y2 EMERGENZA
GIALLO/ROSSO TYPE 1, 4, 4X

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	COMANDO FRONTALE LUCCHETTABILE	UL 486A	[American Standard] Wire Connectors
Serie commerciale	Serie COMMAND	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Descrizione sintetica	COMANDO FRONTALE LUCCHETTABILE	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Materiale	TERMOPLASTICO	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Grado di protezione IP	IP65	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipo	EMERGENZA	UL 60947-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 1: General rules
Colore	GIALLO/ROSSO	UL 60947-4-1	[American Standard] Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and Motor-Starters - Electromechanical Contactors and Motor-Starters
Taglia interruttore	Y2	CSA C22.2 No. 60947-1-13	[Canadian Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tensione nominale	690V	CSA C22.2 No. 60947-4-1-14	[Canadian Standard] Low-voltage switchgear and controlgear - Part 4-1: Contactors and motor-starters - Electromechanical contactors and motor-starters
Diametro	standard	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Dimensioni	67x67mm	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Note1	TYPE144X	DIRECTIVE LOW	[European Directives] Low Voltage
Flangia	67X67MM		

VOLTAGE 2014/35 Directive
/UE