Serpentine Light

FRONT



Serpentine Light by Front is an elegant suspension lamp with an airy design inspired by the twists and turns of paper. Its flowing, translucent form creates the illusion of an endless upward spiral, diffusing light evenly for a soft, natural glow. Ideal for dining tables, hallways, or offices, it adds a touch of perpetual movement to any space.

Detailing




Serpentine light is a fun and simple looking design created with elaborate twists and turns.

Colours

White

Serpentine Light / 8 Large

Dimensions



Product

WIDTH 68cm | 26.8"
HEIGHT 81cm | 31.9"
DEPTH 68cm | 26.8"
WEIGHT NETTO 0.7kg | 1.54lbs

Packaging

WIDTH 83cm | 32.7"
HEIGHT 83.5cm | 32.9"
CUBAGE 0.58m^3 | 20.31ft^3
LENGTH 83cm | 32.7"
WEIGHT 7kg | 15.43lbs

Technical CE

MATERIAL
Shade from printed non-woven PES, coated steel pendant

ENERGY LABEL
E

LIGHTSOURCE TYPE
LED Bulb

LIGHTSOURCE INCLUDED
Yes

NUMBER OF LIGHTSOURCES
1

INPUT VOLTAGE
220-240V

FREQUENCY
50/60

MAX POWER CONSUMPTION
11W

LAMPHOLDER
E27

RECOMMENDED LIGHTSOURCE
LED Bulb up to 20W

LIFETIME
15000 hours

CABLE COLOUR
Black

CABLE LENGTH
250cm | 98.4"

CANOPY
Pebble II Black, ABS

CHROM X
0.4361

CHROM Y
0.4114

COLOUR TEMPERATURE
2700 K (max)

CRI
95

LIGHT DIRECTION
All directions

LIGHT OUTPUT
1158 lm

R9
64

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

CE

Technical UL

MATERIAL

Shade from printed non-woven PES, coated steel pendant

LIGHTSOURCE TYPE

LED Bulb

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

110-130V

FREQUENCY

60

MAX POWER CONSUMPTION

11W

LAMPHOLDER

E26

RECOMMENDED LIGHTSOURCE

UL Listed SBLED Bulb up to 23W

LIFETIME

25000 hours

CABLE COLOUR

Black

CABLE LENGTH

250cm | 98.4"

CANOPY

Pebble II Black, ABS

CHROM X

0.4361

CHROM Y

0.4114

COLOUR TEMPERATURE

2700 K (max)

CRI

95

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1158 lm

R9

64

DIMMING & LIGHTING CONTROL


Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

c UL us LISTED

Serpentine Light / 8 Small

Dimensions



Product

WIDTH 46cm | 18.1"
HEIGHT 60cm | 23.6"
DEPTH 46cm | 18.1"
WEIGHT NETTO 0.3kg | 0.66lbs

Packaging

WIDTH 67cm | 26.4"
HEIGHT 68cm | 26.8"
CUBAGE 0.31m^3 | 10.78ft^3
LENGTH 67cm | 26.4"
WEIGHT 4kg | 8.82lbs

Technical CE

MATERIAL
Shade from printed non-woven PES, coated steel pendant

LIGHTSOURCE TYPE
Incandescent

LIGHTSOURCE INCLUDED
Yes

NUMBER OF LIGHTSOURCES
1

INPUT VOLTAGE
220-240V

FREQUENCY
50/60

MAX POWER CONSUMPTION
11W

LAMPHOLDER
E27

RECOMMENDED LIGHTSOURCE
LED Bulb up to 20W

LIFETIME
15000 hours

CABLE COLOUR
Black

CABLE LENGTH
250cm | 98.4"

CANOPY
Pebble II Black, ABS

CHROM X
0.46

CHROM Y
0.42

COLOUR TEMPERATURE
2700 K (max)

CRI
85

LIGHT DIRECTION
All directions

LIGHT OUTPUT
1137 lm

DIMMING & LIGHTING CONTROL
Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

CE

Technical UL

MATERIAL

Shade from printed non-woven PES, coated steel pendant

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

110-130V

FREQUENCY

60

MAX POWER CONSUMPTION

11W

LAMPHOLDER

E26

RECOMMENDED LIGHTSOURCE

UL Listed SBLED Bulb up to 23W

LIFETIME

25000 hours

CABLE COLOUR

Black

CABLE LENGTH

250cm | 98.4"

CANOPY

Pebble II Black, ABS

CHROM X

0.46

CHROM Y

0.41

COLOUR TEMPERATURE

2700 K (max)

CRI

95

LIGHT DIRECTION

All directions

LIGHT OUTPUT

970 lm

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

c UL us LISTED

Technical

MATERIAL

Shade from printed non-woven PES, coated steel pendant

Dimming & Lighting Control

Mains dimmable with compatible light source

Compatible models: 8 Large CCC, 8 Large CE, 8 Large UL, 8 Small CCC, 8 Small CE, 8 Small UL
