

Scheda Tecnica

CODICE 70581

MICROSOL T 1500-V0

Termoconvettori miniaturizzati da
installazione



Certificazioni

Dati tecnici e prestazionali

Corrente assorbita max (A)	6,5	Peso (Kg)	4,5
Frequenza (Hz)	50	Potenza assorbita max (W)	1500
Grado Protezione IP	X4	Potenza assorbita med(W)	1000
Isolamento	I° classe	Potenza assorbita min (W)	500
		Tensione (V)	230

Dimensioni

Dimensione A (mm)	723
Dimensione B (mm)	258
Dimensione C (mm)	109

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Scheda Tecnica

CODICE 70581

MICROSOL T 1500-V0

Termoconvettori miniaturizzati da
installazione



Descrizione

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com