




Stile next 503

IP 66 ◆ IK 06 1J xx3 C€

Possibile scelta di 3 differenti serigrafie colorate: nero – grigio HT – Corten.
Predisposto per singolo ingresso alimentazione.

Possible choice of serigraphed glass in 3 different colours: black – HT grey – Corten. Single cable entry at the back.

Possibilité de choisir entre 3 sérigraphies colorées différentes : noir – gris HT – corten. Entrée d'alimentation simple.



4

LED

310 lm 3W
real output lm 68

A+ A+ A+

Specif.


CL.I €

Col.



Vetro/Glass
LL641C□
LL641C2□
LL641CG□
LL641CK□

led colour
N = (4000K)
3 = (3000K, lm -5%)
2 = (2700K, lm -5%)



LED

720 lm 6W
real output lm 170

A+ A+ A+

CL.I €

LL641D□

led colour
N = (4000K)
3 = (3000K, lm -5%)




Stile next 506E

IP 66 ◆ IK 06 1J xx3 C€

Predisposto per doppio ingresso alimentazione.

Double cable entry at the back.

Possibilité alimentation double entrée.



4

LED

720 lm 6W
real output lm 283

A+ A+ A+

Specif.

CL.I €

Col.

Vetro/Glass

LL651D□

LED


270 lm 3W
real output lm 96

A+ A+ A+

CL.I €

LL6513□

led colour
N = (4000K)
3 = (3000K, lm -5%)




Stile next 506L

IP 66 ◆ IK 06 1J xx3 C€

Possibile scelta di 3 differenti serigrafie colorate: nero – grigio HT – Corten.
Predisposto per doppio ingresso alimentazione.

Possible choice of serigraphed glass in 3 different colours: black – HT grey – Corten. Double cable entry at the back.

Possibilité de choisir entre 3 sérigraphies colorées différentes : noir – gris HT – corten. Possibilité alimentation double entrée.



4

LED

720 lm 6W
real output lm 217

A+ A+ A+

Specif.

CL.I €

Col.



Vetro/Glass

LL661D□
LL661D2□
LL661DG□
LL661DK□

led colour
N = (4000K)
3 = (3000K, lm -5%)
2 = (2700K, lm -5%)

LED


270 lm 3W
real output lm 94

A+ A+ A+

CL.I €

LL6613□

led colour
N = (4000K)
3 = (3000K, lm -5%)



Stile next 503 asimmetrico

IP 66 ◆ IK 06 1J xx3 C€

Possibile scelta di 3 differenti serigrafie colorate: nero – grigio HT – Corten.
Predisposto per singolo ingresso alimentazione. Deflettore in alluminio primario pressofuso EN-AB44100.

Possible choice of serigraphed glass in 3 different colours: black – HT grey – Corten. Single cable entry at the back. Reflector made of EN-AB44100 die-cast aluminium primary alloy.

Possibilité de choisir entre 3 sérigraphies colorées différentes : noir – gris HT – corten. Entrée d'alimentation simple. Réflecteur en aluminium primaire injecté EN-AB44100.



4

LED

310 lm 3W
real output lm 45

A+ A+ A+

Specif.

CL.I €

Col.



Vetro/Glass

LL643C□
LL643C2□
LL643CG□
LL643CK□

led colour
N = (4000K)
3 = (3000K, lm -5%)
2 = (2700K, lm -5%)

