


Castore suspension 35



IP20 ⊕ ∰ ♥ № @ @ c€ Dimmerable: +**0**-

TECHNICAL DRAWINGS



DESIGN BY

Michele De Lucchi, Huub Ubbens

DESCRIPTION

The spherical diffuser design is enhanced by a removable-fitting and tapering luminous stem, that makes a sweet transition from the strong diffuser light to the blind lamp structure area. Ceiling rose and stem in thermoplastic resin, blown glass diffuser.

Article Code:	1052010A	Material:	Blown glass,
Colour:	White		polycarbonate
Installation:	Suspension	Series:	Design
Environment:	Indoor	Area contract:	Hospitality, Retail Residential
		Emission:	Diffused
DIMENSIONS			
Height:	cm 83	Glow Wire Test:	750
Base Diameter:	cm 15		
Max Height from ceiling:	cm 233		
NOT INCLUDED SOUR	CES		
Category:	HALO	Color Rendering:	1a
Number:	1	Color temperature (K):	2900K
Watt:	150W		
Lbs:	Qt32		
Socket:	E27		
Duration (h):	2000h		
	-		
ALTERNATIVE SOURCE	S		
	LED		
Category:			
Category: Number:	LED 1		
Category: Number: Watt:	LED 1 21W		
Category: Number: Watt: Delivered lumens output (li	LED 1 21W		
Category: Number: Watt: Delivered lumens output (li	LED 1 21W m): 2452Im 2		
Category: Number: Watt: Delivered lumens output (lı Type: Socket:	LED 1 21W m): 2452lm		
Category: Number: Watt: Delivered lumens output (lı Type: Socket: Class:	LED 1 21W m):2452lm 2 E27		
Category: Number: Watt: Delivered lumens output (li Type: Socket: Class: LUMINAIRE	LED 1 21W m):2452lm 2 E27	Delivered lumens output (Im): 2431lm
Category: Number: Watt: Delivered lumens output (lı Type: Socket: Class: LUMINAIRE Watt:	LED 1 21W m): 2452lm 2 E27 A	Delivered lumens output (CCT:	Im): 2431lm 3000K
Category: Number: Watt: Delivered lumens output (li Type: Socket: Class: LUMINAIRE Watt:	LED 1 21W m): 2452lm 2 E27 A	CCT:	
Category: Number: Watt: Delivered lumens output (li Type: Socket: Class: LUMINAIRE Watt:	LED 1 21W m): 2452lm 2 E27 A	CCT: Efficiency:	3000K 85%
Number: Watt: Delivered lumens output (lı Type: Socket:	LED 1 21W m): 2452lm 2 E27 A	CCT:	3000K

Available in four sizes.